

Zincphosphat-primer GK-02

High-quality activ-primer with selected antirust pigments. Weatherproof paint for all priming-works on steel and iron; for indoor and outdoor applications. Lead and cromate free. Quick drying. Extremely well suitable for all priming works on industrial plants, vehicles and building constructions.

Delivery units:	1,0 l 2,5 l 5,0 l 14,0 kg 37,0 kg
Colour shades:	greengreen, redbrown, black, white, yelloworange; special and some RAL colour shades.
Specific gravity:	200 – 300 g per square metre
Density:	approx. 1,25 – 1,4 kg/l
VOC - EU - limiting value:	cat. B/c: 540 g/l (2007) This product contains max. 540 g/l VOC.
Solvent:	VK-30
Coating build:	min. 30 – 40 µm per coat
Substrate:	clean, free of rust and scale, most suitable sandblasted Sa 2 ½
Paint recommendation:	for steel 1 x primer, 1 – 2 x cover varnish LK-12
Application:	apply evenly via brush, roller or spraygun, also airless and electric statically as adjusted.
Drying Time:	after approx. 20 – 30 minutes dust dry, thoroughly dry over night
Flashpoint:	above +23°C (69,8°F)
Safety- and danger marks:	see safety data sheet

TM/GK-02 revised: 25.02.09 rei/in / printout: 25.02.09/GB